



SIFANG

TRACTORS



浙江四方集团有限公司

ZHEJIANG SIFANG GROUP CORP., LTD.

浙江四方进出口有限公司

ZHEJIANG SIFANG IMP.& EXP.CO., LTD.



SIFANG SERIES A SF504A/SF604A/SF704A/SF804A



性能参数 SPECIFICATION

Tractor model	Unit	SF504A	SF604A	SF704A	SF804A
Engine		XINCHAI 4-cylinder	XINCHAI 4-cylinder	XINCHAI 4-cylinder	XINCHAI 4-cylinder
Engine model		498	498T	498T	498T
Engine power	HP/KW	50/36.8	60/44.2	70/52	80/59
Fuel tank capacity	L	60	60	60	60
Air cleaner		External wet type with prefilter	External wet type with prefilter	External wet type with prefilter	External wet type with prefilter
Transmission					
Driving type		4WD	4WD	4WD	4WD
Clutch		10 inch dual clutch	10 inch dual clutch	10 inch dual clutch	10 inch dual clutch
Gearbox		12F+12R collar shift	12F+12R collar shift	12F+12R collar shift	12F+12R collar shift
PTO	r/min	540/720	540/720	540/720	540/720
PTO shaft		6 splines	6 splines	6 splines	6 splines
Brakes					
Driving brake		Dry disk	Dry disk	Dry disk	Dry disk
Parking brake		Foot-operated parking brake	Foot-operated parking brake	Foot-operated parking brake	Foot-operated parking brake
Air brake (trailer brake)		•	•	•	•
Hydraulics					
Type		Force and position separate control	Force and position separate	Force and position separate control	Force and position separate control
Hydraulic lifting capacity at	KG	845	1013	1273	1442
No. of multiway valves		2	2	2	2
ROPS		•	•	•	•
Sunshade		•	•	•	•
Cabin and A/C		•	•	•	•
Tyre					
Front		8.3-20	8.3-20	8.3-24	8.3-24
Rear		12.4-28	12.4-28	12.4-32	12.4-32
Dimension & weight					
Length	mm	3710	3710	3710	3710
Width	mm	1630	1630	1630	1630
Height	mm	2470	2470	2470	2470
Wheelbase	mm	1960	1960	1960	1960
Mini ground clearance	mm	340	340	400	400
Gross structure weight	KG	2120	2120	2150	2150
Others					
Front ballast		•	•	•	•
Rear ballast		•	•	•	•
Drawbar		•	•	•	•



SIFANG SERIES B

SF504B/SF604B/SF704B



性能参数 SPECIFICATION

Tractor model	Unit	SF504B	SF604B	SF704B
Engine		XINCHAI 4-cylinder	XINCHAI 4-cylinder	XINCHAI 4-cylinder
Engine model		498	498	498T
Engine power	HP/KW	50/36.8	60/44.2	70/52
Fuel tank capacity	L	60	60	60
Air cleaner		External wet type with prefilter	External wet type with prefilter	External wet type with prefilter
Transmission				
Driving type		4WD	4WD	4WD
Clutch		10 inch single clutch	10 inch single clutch	10 inch single clutch
Gearbox		8F+2R	8F+2R	8F+2R
PTO	r/min	540/720	540/720	540/720
PTO shaft		6 splines/8 splines	6 splines/8 splines	6 splines/8 splines
Brakes				
Driving brake		Dry disk	Dry disk	Dry disk
Parking brake		Foot-operated parking brake	Foot-operated parking brake	Foot-operated parking brake
Air brake (trailer brake)		•	•	•
Hydraulics				
Type		Force and position separate control	Force and position separate control	Force and position separate control
Hydraulic lifting capacity at	KG	845	1013	1273
No. of multiway valves		2	2	2
ROPS		•	•	•
Sunshade		•	•	•
Cabin and A/C		•	•	•
Tyre				
Front		7.5-16	7.5-16	8.3-24
Rear		11.2-28	11.2-28	11-32
Dimension & weight				
Length	mm	3600	3655	3600
Width	mm	1640	1660	1640
Height	mm	2470	2600	2470
Wheelbase	mm	1955	2130	2130
Mini ground clearance	mm	360	430	430
Gross structure weight	KG	1960	2120	2120
Others				
Front ballast		•	•	•
Rear ballast		•	•	•
Drawbar		•	•	•



SIFANG SERIES C SF354C/SF404C/SF454C/SF504C



性能参数 SPECIFICATION

Tractor model	Unit	SF354C	SF404C	SF454C	SF504C
Engine		XINCHAI 4-cylinder LONGCHAI 2-cylinder	XINCHAI 4-cylinder	XINCHAI 4-cylinder	XINCHAI 4-cylinder
Engine model		490(4-cylinder) 2110(2-cylinder)	490	490	495
Engine power	HP/KW	35/25.8	40/29.5	45/33.1	50/36.8
Fuel tank capacity	L	60	60	60	60
Air cleaner		External wet type with prefilter	External wet type with prefilter	External wet type with prefilter	External wet type with prefilter
Transmission					
Driving type		4WD	4WD	4WD	4WD
Clutch		9 inch single clutch	9 inch single clutch	9 inch single clutch	9 inch single clutch
Gearbox		8F+2R	8F+2R	8F+2R	8F+2R
PTO	r/min	540/720	540/720	540/720	540/720
PTO shaft		6 splines/8 splines	6 splines/8 splines	6 splines/8 splines	6 splines/8 splines
Brakes					
Driving brake		Dry disk	Dry disk	Dry disk	Dry disk
Parking brake		Foot-operated parking brake	Foot-operated parking brake	Foot-operated parking brake	Foot-operated parking brake
Air brake (trailer brake)		•	•	•	•
Hydraulics					
Type		Force and position separate control	Force and position separate control	Force and position separate control	Force and position separate control
Hydraulic lifting capacity at	KG	607	678	760	845
No. of multiway valves		1	2	2	2
ROPS		•	•	•	•
Sunshade		•	•	•	•
Cabin and A/C		\	\	\	\
Tyre					
Front		6.0-16	6.0-16	6.0-16	7.5-16
Rear		11.2-24	11.2-24	11.2-24	11.2-28
Dimension & weight					
Length	mm	3350(4-cylinder)/3120(2-cylinder)	3350	3350	3380
Width	mm	1460	1460	1460	1500
Height	mm	2350	2350	2350	2370
Wheelbase	mm	1830(4-cylinder)/1627(2-cylinder)	1830	1830	1850
Mini ground clearance	mm	320	320	320	340
Gross structure weight	KG	1525	1590	1590	1750
Others					
Front ballast		•	•	•	•
Rear ballast		•	•	•	•
Drawbar		•	•	•	•